



```

import numpy as np
import matplotlib.pyplot as plt
from matplotlib.animation import FuncAnimation
from matplotlib.widgets import Slider, Button
from scipy.integrate import solve_ivp

# Constants and default parameters
g = 9.81

# Default parameters for masses, lengths and initial angles (in radians)
default_params = {
    'm1': 1.0,
    'm2': 1.0,
    'l1': 1.0,
    'l2': 1.0,
    'theta1': np.pi / 2,
    'theta2': np.pi / 2,
    'omega1': 0.0,
    'omega2': 0.0,
}

def double_pendulum_derivs(t, y, m1, m2, l1, l2):

```

```

"""Returns the derivatives for the double pendulum system.

y = [theta1, theta2, omegal, omega2]
"""
theta1, theta2, omegal, omega2 = y

delta = theta2 - theta1

denom1 = (m1 + m2) * l1 - m2 * l1 * np.cos(delta)**2
domegal_dt = (m2 * l1 * omegal**2 * np.sin(delta) * np.cos(delta) +
               m2 * g * np.sin(theta2) * np.cos(delta) +
               m2 * l2 * omega2**2 * np.sin(delta) -
               (m1 + m2) * g * np.sin(theta1)) / denom1

denom2 = (l2 / l1) * denom1
domega2_dt = (- m2 * l2 * omega2**2 * np.sin(delta) * np.cos(delta) +
                (m1 + m2) * g * np.sin(theta1) * np.cos(delta) -
                (m1 + m2) * l1 * omegal**2 * np.sin(delta) -
                (m1 + m2) * g * np.sin(theta2)) / denom2

return [omegal, omega2, domegal_dt, domega2_dt]

def simulate(params, t_max=20, dt=0.02):
    """Simulate the double pendulum motion with given parameters."""
    t_span = (0, t_max)
    t_eval = np.arange(0, t_max, dt)
    y0 = [params['theta1'], params['theta2'], params['omegal'],
    params['omega2']]
    sol = solve_ivp(double_pendulum_derivs, t_span, y0, args=(params['m1'],
    params['m2'], params['l1'], params['l2']),
                    t_eval=t_eval, method='RK45')
    return sol.t, sol.y

# Initial simulation data
t, y = simulate(default_params)
theta1_vals = y[0]
theta2_vals = y[1]

def get_positions(theta1, theta2, l1, l2):
    """Calculate positions of pendulum bobs."""
    x1 = l1 * np.sin(theta1)
    y1 = -l1 * np.cos(theta1)
    x2 = x1 + l2 * np.sin(theta2)
    y2 = y1 - l2 * np.cos(theta2)
    return x1, y1, x2, y2

# Create the figure and the animation axes
fig, ax = plt.subplots(figsize=(8, 8))
plt.subplots_adjust(left=0.1, bottom=0.35)
ax.set_xlim(-3, 3)
ax.set_ylim(-3, 3)

```

```
ax.set_aspect('equal')
ax.set_title('Double Pendulum Simulation')

# Initialize line and bob markers
line, = ax.plot([], [], 'o-', lw=2)
trace, = ax.plot([], [], '--', lw=1, color='gray') # Optional trace of
second bob
trace_x, trace_y = [], []

def init():
    line.set_data([], [])
    trace.set_data([], [])
    return line, trace

# Animation update function
def update(frame):
    theta1 = thetal_vals[frame]
    theta2 = theta2_vals[frame]
    x1, y1, x2, y2 = get_positions(theta1, theta2, current_params['l1'],
current_params['l2'])
    line.set_data([0, x1, x2], [0, y1, y2])
    trace_x.append(x2)
    trace_y.append(y2)
    trace.set_data(trace_x, trace_y)
    return line, trace

# Create sliders for initial parameters
axcolor = 'lightgoldenrodyellow'
ax_m1 = plt.axes([0.1, 0.25, 0.3, 0.03], facecolor=axcolor)
ax_m2 = plt.axes([0.1, 0.20, 0.3, 0.03], facecolor=axcolor)
ax_l1 = plt.axes([0.1, 0.15, 0.3, 0.03], facecolor=axcolor)
ax_l2 = plt.axes([0.1, 0.10, 0.3, 0.03], facecolor=axcolor)
ax_theta1 = plt.axes([0.6, 0.25, 0.3, 0.03], facecolor=axcolor)
ax_theta2 = plt.axes([0.6, 0.20, 0.3, 0.03], facecolor=axcolor)

slider_m1 = Slider(ax_m1, 'Mass 1', 0.1, 5.0, valinit=default_params['m1'])
slider_m2 = Slider(ax_m2, 'Mass 2', 0.1, 5.0, valinit=default_params['m2'])
slider_l1 = Slider(ax_l1, 'Length 1', 0.5, 3.0,
valinit=default_params['l1'])
slider_l2 = Slider(ax_l2, 'Length 2', 0.5, 3.0,
valinit=default_params['l2'])
slider_theta1 = Slider(ax_theta1, 'Theta 1', 0, 2*np.pi,
valinit=default_params['theta1'])
slider_theta2 = Slider(ax_theta2, 'Theta 2', 0, 2*np.pi,
valinit=default_params['theta2'])

# Dictionary to hold current simulation parameters
current_params = default_params.copy()

def update_simulation(val):
    """Update simulation based on slider values."""

```

```
global t, y, theta1_vals, theta2_vals, trace_x, trace_y, current_params

# Update current parameters from sliders
current_params['m1'] = slider_m1.val
current_params['m2'] = slider_m2.val
current_params['l1'] = slider_l1.val
current_params['l2'] = slider_l2.val
current_params['theta1'] = slider_theta1.val
current_params['theta2'] = slider_theta2.val
current_params['omegal'] = 0.0
current_params['omega2'] = 0.0

# Re-run the simulation with new parameters
t, y = simulate(current_params)
theta1_vals = y[0]
theta2_vals = y[1]

# Clear the trace and reset animation frame index
trace_x.clear()
trace_y.clear()
ani.frame_seq = ani.new_frame_seq()
fig.canvas.draw_idle()

# Call update_simulation when any slider value changes
slider_m1.on_changed(update_simulation)
slider_m2.on_changed(update_simulation)
slider_l1.on_changed(update_simulation)
slider_l2.on_changed(update_simulation)
slider_theta1.on_changed(update_simulation)
slider_theta2.on_changed(update_simulation)

# Button to reset sliders to default values
reset_ax = plt.axes([0.8, 0.05, 0.1, 0.04])
button_reset = Button(reset_ax, 'Reset', color=axcolor, hovercolor='0.975')

def reset(event):
    slider_m1.reset()
    slider_m2.reset()
    slider_l1.reset()
    slider_l2.reset()
    slider_theta1.reset()
    slider_theta2.reset()

button_reset.on_clicked(reset)

# Create the animation
ani = FuncAnimation(fig, update, frames=len(t), init_func=init, interval=20,
blit=True)

plt.show()
```